

# Oil-Only Poly Blend Pillow #WPIL818 - 8" x 18", 20 pillows/package



Use SpillTech® Oil-Only Pillows to absorb high-volume leaks and spills of oil and other petroleum-based liquids on land or water.

### **WPIL818 Specifications**

Dimensions:	8" W x 18" L
Shipping	24" W x 16" L x 11.5" H
Dimensions:	
Sold as:	20 pillows per package
Color:	White
Composition:	Poly Blend
<b>Recycled Content:</b>	100% Post-Industrial Recycled Poly
	Blend Filler
Absorbency:	Up to 23 gal. per package
Absorbency per:	Up to 1.15 gal. per pillow
Weight:	10.5 lbs.
# per Pallet:	35
Incinerable:	Yes
Ship Class:	175

## **Metric Equivalent Specifications**

Dimensions:	20.3cm W x 45.7cm L
Shipping	61cm W x 40.6cm L x 29.2cm H
Dimensions:	
Absorbency:	Up to 87.1 L per package
Absorbency per:	Up to 4.4 L per pillow
Weight:	4.8 kg



Online: spilltech.com Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other)



Email: sales@spilltech.com

## WPIL818 Technical Information

### Warnings & Restrictions:

Color Variance Notice Color may vary.

#### **Regulations and Compliance:**

49 CFR 173.3(c)(2) - The area between a container and a salvage drum used for overpacking must have "sufficient cushioning and absorption material to prevent excessive movement of the damaged package and to eliminate the presence of any free liquid at the time the salvage drum is closed."

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

33 CFR 154.1047(c)(2) - Concerning navigation and navigable waters, a facility which handles, stores or transports Group V petroleum oils must identify response plan resources such as containment booms and other methods.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

#### **Technical Documents:**

(Available at spilltech.com)

Product Data Sheet (PDS) Safety Data Sheet (SDS)







Email: sales@spilltech.com